

NUMARATOARE DIGITALE

[Pentru specificatii tehnice](#)

[CLICK aici](#)

Producator **SELET SENSOR**

Numarator simplu cu presetare: CT124



Dimensiuni (inclusiv terminale)	48 x 48 x 100 mm
Decupare in panou	45,5 x 45,5 mm
Alimentare	15-30 Vcc 24 Vca 110 Vca 220 Vca
Putere consumata	max. 1,5 VA
Alimentare senzor extern	12 Vcc $\pm 10\%$, 50 mA
Intrari	NAMUR / MICRO / NPN / PNP
Frecventa max. de numarare	2 KHz
Iesire	releu, contacte 5A/ 250V
Carcasa	PVC DIN 43700
Panou frontal	plexiglas
Grad protectie	butoane pushwheel
Afisaj	IP 54 LED, 4 cifre, h=9 mm

Numarator presetabil: selectare ciclu automat/manual, frecventa maxima de numarare

Numarator totalizator: CTY60



Dimensiuni (inclusiv terminale)	96 x 48 x 100 mm
Decupare in panou	92,3 x 45,5 mm
Alimentare	15-30 Vcc 24 Vca 110 Vca 220 Vca
Putere consumata	max. 3 VA
Alimentare senzor extern	12 Vcc, 50 mA
Intrari	NAMUR / MICRO / NPN / PNP
Frecventa max. de numarare	10 KHz
Tastatura programare	4 taste interne
Carcasa	PVC DIN 43700
Panou frontal	plexiglas
Grad protectie	IP 54
Afisaj	LED, 6 cifre, h=12 mm

Numarator totalizator programabil cu microprocesor

Numarator totalizator: CBM6



Dimensiuni (inclusiv terminale)	96 x 48 x 100 mm
Decupare in panou	92,3 x 45,5 mm
Alimentare	15-30 Vcc 24 Vca 110 Vca 220 Vca
Putere consumata	max. 3 VA
Alimentare senzor extern	12 Vcc, 50 mA
Intrari	NAMUR / MICRO / NPN / PNP
Frecventa max. de numarare	10 KHz
Iesiri (CBM63)	2 x releu, contacte 5A/ 250 V
Iesiri (CBM65)	4 releu 2 x contacte 5A/ 250 V + 2 x contacte 1A/ 250 V
Tastatura programare	4 taste
Carcasa	PVC DIN 43700
Panou frontal	policarbonat
Grad protectie	IP 54
Afisaj	LED, 6 cifre, h=12 mm
Comunicatie seriala	CBM6_/R
Iesire analogica	CBM6_/LE

CBM60: numai indicator

CBM63: numarator cu 2 presetari

CBM65: numarator cu 4 presetari

NUMARATOARE, TEMPORIZATOARE, NUMARATOARE DE ROTATII

Numarator – temporizator programabil: CTY12



Dimensiuni (inclusiv terminale)	48 x 48 x 100 mm
Decupare in panou	45,5 x 45,5 mm
	15-30 Vcc
Alimentare	24 Vca
	110 Vca
	220 Vca
Putere consumata	max. 1,5 VA
Alimentare senzor extern	12 Vcc, 50 mA
Intrari	NAMUR / MICRO / NPN / PNP
Frecventa max. de numarare	5 KHz
Temporizator (baza de timp)	h, min, sec (msec)
Iesire	releu
	contacte 1A/ 250 V
Tastatura programare	4 taste
Carcasa	PVC DIN 43700
Panou frontal	policarbonat
Grad protectie	IP 54
Afisaj	LED, 4 + 4 cifre, h=9 mm

Numarator/ temporizator programabil cu 2 afisaje, set point + numarare

Numarator – temporizator programabil: CTY52



Dimensiuni (inclusiv terminale)	72 x 72 x 100 mm
Decupare in panou	67 x 67 mm
	15-30 Vcc
Alimentare	24 Vca
	110 Vca
	220 Vca
Putere consumata	max. 3 VA
Alimentare senzor extern	12 Vcc, 50 mA
Intrari	NAMUR / MICRO / NPN / PNP
Frecventa max. de numarare	5 KHz
Temporizator (baza de timp)	h, min, sec (msec)
Iesire	relee
	2 x contacte 2A/ 250 V
Tastatura programare	4 taste
Carcasa	PVC DIN 43700
Panou frontal	policarbonat
Grad protectie	IP 54
Afisaj	LED, 4 + 4 cifre, h=12 mm

Numarator/ temporizator programabil cu 2 afisaje, set point + numarare

Numarator multifunctional programabil: XTM1



Dimensiuni (inclusiv terminale)	48 x 48 x 100 mm
Decupare in panou	45,5 x 45,5 mm
	15-30 Vcc
Alimentare	24 Vca
	110 Vca
	220 Vca
Putere consumata	max. 1,5 VA
Alimentare senzor extern	12 Vcc, 50 mA
Intrari	NAMUR / MICRO / NPN / PNP
Frecventa max. de numarare	5 KHz
Temporizator (baza de timp)	h, min, sec (msec)
Frecventmetru	Hz, rot/min, productie/ora
Iesire	relee
	2 x contacte 1A/ 250 V
Tastatura programare	4 taste
Carcasa	PVC DIN 43700
Panou frontal	policarbonat
Grad protectie	IP 54
Afisaj	LED, 5 cifre, h=9 mm

XTM10: Numarator – temporizator - numarator de rotatii: numai indicator

XTM13: Numarator – temporizator - numarator de rotatii cu 2 presetari

NUMARATOARE, TEMPORIZATOARE, NUMARATOARE DE ROTATII

Numarator multifunctional programabil: XTM5



Dimensiuni (inclusiv terminale)	72 x 72 x 100 mm
Decupare in panou	67 x 67 mm
Alimentare	15-30 Vcc 24 Vca 110 Vca 220 Vca
Putere consumata	max. 1,5 VA
Alimentare senzor extern	12 Vcc, 50 mA
Intrari	NAMUR / MICRO / NPN / PNP
Frecventa max. de numarare	5 KHz
Temporizator (baza de timp)	h, min, sec (msec)
Frecventmetru	Hz, rot/min, productie/ora
Iesire	relee 2 x contacte 1A/ 250 V
Tastatura programare	4 taste
Carcasa	PVC DIN 43700
Panou frontal	policarbonat
Grad protectie	IP 54
Afisaj	LED, 5 cifre, h=9 mm

XTM50: Numarator – temporizator - numarator de rotatii: numai indicator

XTM53: Numarator – temporizator - numarator de rotatii: cu 2 presetari

Numarator multifunctional programabil: XTM6



Dimensiuni (inclusiv terminale)	96 x 48 x 100 mm
Decupare in panou	92,3 x 45,5 mm
Alimentare	15-30 Vcc 24 Vca 110 Vca 220 Vca
Putere consumata	max. 3 VA
Alimentare senzor extern	12 Vcc, 50 mA
Intrari	NAMUR / MICRO / NPN / PNP
Frecventa max. de numarare	5 KHz
Temporizator (baza de timp)	h, min, sec (msec)
Frecventmetru	Hz, rot/min, productie/ora
Iesire	relee 2 x contacte 2A/ 250 V
Tastatura programare	4 taste
Carcasa	PVC DIN 43700
Panou frontal	policarbonat
Grad protectie	IP 54
Afisaj	LED, 5 cifre, h=12 mm

XTM60: Numarator – temporizator - numarator de rotatii: numai indicator

XTM63: Numarator – temporizator - numarator de rotatii: cu 2 presetari

VITEZA, ROTATII, FRECVENTA, NUMARATOARE DE PRODUCTIE

Numarator de rotatii programabil: CGY60



Dimensiuni (inclusiv terminale)	96 x 48 x 100 mm
Decupare in panou	92,3 x 45,5 mm
Alimentare	15-30 Vcc 24 Vca 110 Vca 220 Vca
Putere consumata	max. 3 VA
Alimentare senzor extern	12 Vcc, 50 mA
Intrari	NAMUR / MICRO / NPN / PNP
Frecventa max. de numarare	10 KHz
Tastatura programare	4 taste interne
Carcasa	PVC DIN 43700
Panou frontal	plexiglas
Grad protectie	IP 54
Afisaj	LED, 6 cifre, h=12 mm

Numarator de rotatii/ indicator de viteza programabil cu microprocesor

Indicator de viteza programabil: IVM6



Dimensiuni (inclusiv terminale)	96 x 48 x 100 mm
Decupare in panou	92,3 x 45,5 mm
Alimentare	15-30 Vcc 24 Vca 110 Vca 220 Vca
Putere consumata	max. 3 VA
Alimentare senzor extern	12 Vcc, 50 mA
Intrari	NAMUR / MICRO / NPN / PNP
Frecventa max. de numarare	10 KHz
Frecventmetru	Hz, rot/min, productie/ora
Iesiri (IVM63)	2 x releu, contacte 5A/ 250 V
Iesiri (IVM65)	4 releu 2 x contacte 5A/ 250 V + 2 x contacte 1A/ 250 V
Tastatura programare	4 taste
Carcasa	PVC DIN 43700
Panou frontal	policarbonat
Grad protectie	IP 54
Afisaj	LED, 6 cifre, h=12 mm
Comunicatie seriala	IVM6 _R
Iesire analogica	IVM6 _LE

IVM60: numai indicator

IVM63: indicator de viteza cu 2 presetari

IVM65: indicator de viteza cu 4 presetari

Distribuitor:

SC SYSCOM 02 SRL Bucuresti

Tel: 021 410 5281; 021 444 1241; GSM: 0722 725 659

Fax: 021 410 5281; 021 444 1241;

e-mail: syscom02@automatizariindustriale.ro

www.automatizariindustriale.ro